



Are you looking for the best available method to deal with weed (bluegrass, moss etc.) or an oily upper layer? Do you want to preserve your sports pitch in excellent condition? The Vstrong can do it all. We produce our Vstrong scarifying machine in the same innovative manner as our Combinator. With this machine, we not only improve on the already proven technology, but also the operating speed (to 12 km/h) and the reliability of the Vstrong will appeal to a professional like you. If you are thinking of chemical-free weed management and minimization of waste flows, then you should consider using the Vstrong.



By means of our patented roller pendulum system, you can easily control the operating depth. As a unique bonus, we have provided the scarifying machine with a hydraulic adjustable cover. This is ideal when you are required to scarify near the edges and corners of a pitch.

The CombiRotor® is the beating heart of the machine. With the Vstrong you are able to attain an operating depth of 5 cm. In combination with the reversed rotation direction, it is guaranteed the Vstrong will never miss a single inch. After the scarified material has dried, you can load or remove the material. Why do we suggest you let the scarified material dry first? Since waste removal is costly and it is a waste of valuable nutrients for the grass if you decide to immediately remove the material.

THE WORKER IS KING




Vstrong Specifications:

Type	VS120	VS160	VS200	VS240
Working width	120 cm / 47"	160 cm / 63"	200 cm / 79"	240 cm / 94"
Working depth	0 - 5 cm / 0 - 2"	0 - 5 cm / 0 - 2"	0 - 5 cm / 0 - 2"	0 - 5 cm / 0 - 2"
Centre to centre distance scarifier blades	2,5 / 5,0 cm 1" / 2"	2,5 / 5,0 cm 1" / 2"	2,5 / 5,0 cm 1" / 2"	2,5 / 5,0 cm 1" / 2"
Afmetingen (l x b x h)	140 x 165 x 100 cm / 55 x 65 x 39"	160 x 205 x 110 cm / 63 x 81 x 43"	170 x 245 x 110 cm / 67 x 96 x 43"	170 x 285 x 110 cm / 67 x 112 x 43"
Gewicht	350 kg / 775 lbs	500 kg / 1105 lbs	750 kg / 1653 lbs	900 kg / 1990 lbs
Benodigd vermogen	> 40 hp	> 45 hp	> 65 hp	> 90 hp
Koppeling	three-point hitch cat. II	three-point hitch cat. II	three-point hitch cat. II	three-point hitch cat. II

The following specification is applicable to every Vstrong model:

Hydraulics	1x double working hydraulic valve transport hood			
Collection box	200 liter	265 liter	-	-



THE WORKER IS KING